



Larch Alaska

PRODUCT DETAILS

Species	Larch
Construction	3-layer engineered (softwood core)
Texture	Brushed
Patterns	Boards / Boards in mixed widths



Boards



Boards
in
mixed
widths

Boards Width	160mm / 195mm / 245mm
Boards Lengths	Fixed 2200mm
Herringbone sizes	Not available
Chevron sizes	Not available
Depth / top layer (+/- 0.5mm)	15 / 4mm (15mm depth with a wear layer of +/- 4mm)**
	* Maximum board width: 220mm
	** Maximum board width: 285mm

Edge profile	Micro bevel
--------------	-------------

TECHNICAL CRITERIA

Origin	Germany
Formaldehyde Emission	E1 Engineered floors classified as E1 do not emit more than 0.1 ppm of formaldehyde into the ambient air and are 100% safe for interior use.
Certification	PEFC, EU and UK Timber Regulation compliant

GRADES CRITERIA

Grades	Knotty (Larch)
Knotty (Larch)	Frequent knots including filled knots, typical for softwood timber.



Larch Alaska, brushed



STAIR SOLUTIONS



Nose Vr
Victorian Bullnose, round



Nose Vp
Victorian Bullnose, pencil round



Nose Sp
Square Nose (no overhang), pencil round

COLOUR VARIATION

Non-fumed Non-fumed tones have less variation in colour compared to fumed tones. Please note, the natural variation can vary between batches.

Please read our installation guide for information on how to achieve a harmonious looking floor.

PACK SIZE

2.11m² for 160mm width,
2.57m² for 195mm width,
3.23m² for 245mm width

INSTALLATION METHODS

Fixed installation Secretly nailed or fully bonded.

Floating on underlay Possible, up to a board width of 245mm.

Fully bonded over underfloor heating Suitable for installation over underfloor heating. Floors must be fully bonded to the substrate. The temperature of the floor surface must not exceed 27 degrees.

Please refer to our comprehensive [installation guide](#) for more information.

RECOMMENDED OIL FOR TOPCOAT

Osmo Polyx Hardwax Oil Clear Semi-Matt 3065 applied by roller/ brush,
Osmo Polyx Hardwax Oil Clear Matt 3062 applied by roller/ brush

Please read our guide on post installation requirements and application of the topcoat of oil.

MAINTENANCE

For regular damp mopping use the Osmo Wash & Care Soap

Please read the maintenance guide/o+m available from Waxed Floors.