





Oak Barley

PRODUCT DETAILS

Species	European Oak
Construction	Plywood engineered (birch)
Texture	Brushed / Treehouse
Patterns	Boards / Boards in mixed widths / Chevron / Herringbone
	
Boards	
Boards in mixed widths	
Chevron	



Oak Barley, brushed



Treehouse Oak Barley

Boards Width	180mm / 220mm / 240mm / 260mm / 300mm
Boards Lengths	Varied 1800 – 2400mm
Herringbone sizes	90 x 450mm / 120 x 600mm / 150 x 750mm
Chevron sizes	120 x 600mm / 150 x 750mm
<hr/>	
Depth / top layer (+/- 0.5mm)	15 / 4mm (15mm depth with a wear layer of +/- 4mm), 20 / 5mm (20mm depth with a wear layer of +/- 5mm)
* Maximum board width: 220mm	
** Maximum board width: 285mm	
<hr/>	
Edge profile	Micro bevel

TECHNICAL CRITERIA

Origin	Holland
Formaldehyde Emission	E1 Engineered floors classified as E1 do not emit more than 0.1 ppm of formaldehyde into the ambient air and are 100% safe for interior use.
Certification	FSC, EU and UK Timber Regulation compliant

The company reserves the right to change this specification at any time without prior notice to third parties. The images are intended as a guide only and should not be regarded as absolutely accurate.

Waxed Floors, 92 Battersea Rise, London SW11 1EJ,
T. +44 20 7738 1620, sales@waxedfloors.co.uk
waxedfloors.co.uk

GRADES CRITERIA

Grades	Rustic / Rustic A / Premier
Rustic	<p>Large and frequent knots including large, filled knots become a feature of the overall look. Rustic grade allows for a wide range of variation in colour and grain. The colour of the filler is intended to compliment the colour of the wood and may vary from batch to batch.</p>
	<ul style="list-style-type: none"> • Knots up to 80mm • Filled knots, cracks, and other imperfections • Centre core • Natural colour variation • Sapwood up to max. 25mm (on long side of boards)
Rustic A	<p>Rustic A grade is a selection of premier grade and 'good' rustic grade material. It contains knots including filled knots up to 40mm in size. The colour of the filler is intended to compliment the colour of the wood.</p>
	<ul style="list-style-type: none"> • Knots up to 40mm, including filled knots • Occasional, small cracks up to 20mm • Natural colour variation • Occasional sapwood up to max. 10mm
Premier	<p>Premier grade has an even appearance with very few, small knots. The natural variation is limited, though can be more visible on fumed oak.</p>
	<ul style="list-style-type: none"> • Occasional knots up to 15mm • Occasional, small cracks up to 20mm • Natural colour variation • No sapwood
	<p>Please note the selection process of prime/ premier grade boards wider than 245mm is usually more relaxed. The aim is to select calm boards with the minimum number of knots and grain variation.</p>

STAIR SOLUTIONS

	Nose Vr Victorian Bullnose, round
	Nose Vp Victorian Bullnose, pencil round
	Nose Se Square Nose (no overhang), bevelled

COLOUR VARIATION

- Fumed**
The production process involves fuming with ammonia. This process results in colour variation between the boards / parquet pieces.

Please read our installation guide for information on how to achieve a harmonious looking floor.

PACK SIZE

Varied, between 1.6-2.5m²

INSTALLATION METHODS

Fully bonded over underfloor heating	Suitable for installation over underfloor heating. Floors must be fully bonded to the substrate. The temperature of the floor surface must not exceed 27 degrees.
Floating on underlay	Possible, up to a board width of 245mm.
Fixed installation	Secretly nailed or fully bonded. Please refer to our comprehensive installation guide for more information.

RECOMMENDED OIL FOR TOPCOAT

Osmo Polyx Hardwax Oil Clear Semi-Matt 3065 applied by roller/ brush

Please read our guide on post installation requirements and application of the topcoat of oil.

MAINTENANCE

For regular damp mopping use the Osmo Wash & Care Soap

Please read the maintenance guide/o+m available from Waxed Floors.