



Oak Carbon Grey

PRODUCT DETAILS


| | |
|--------------|---|
| Species | European Oak |
| Construction | Plywood engineered (birch) |
| Texture | Planed |
| Patterns | Herringbone / Boards / Boards in mixed widths / Chevron |




Herringbone



Boards



Boards in mixed widths



Chevron

| | |
|-------------------|-------------------------------|
| Boards Width | 145mm / 185mm / 285mm / 245mm |
| Boards Lengths | Varied 1500 – 2500mm |
| Herringbone sizes | 85 x 425mm / 145 x 580mm |
| Chevron sizes | 85 x 425mm / 145 x 725mm |

| | |
|-------------------------------|---|
| Depth / top layer (+/- 0.5mm) | 12 / 3mm (12mm depth with a wear layer of +/- 3mm)*, 15 / 4mm (15mm depth with a wear layer of +/- 4mm)**, 20 / 6mm (20mm depth with a wear layer of +/- 6mm) |
| | * Maximum board width: 220mm |
| | ** Maximum board width: 285mm |

| | |
|--------------|--|
| Edge profile | Micro bevel, No bevel (square edge) |
|--------------|--|



Oak Carbon Grey, planed

TECHNICAL CRITERIA








| | |
|-----------------------|---|
| Origin | Holland |
| Formaldehyde Emission | E1 Engineered floors classified as E1 do not emit more than 0.1 ppm of formaldehyde into the ambient air and are 100% safe for interior use. |
| Certification | FSC (Forest Stewardship Council) – certification on request, PEFC, EU and UK Timber Regulation compliant |

GRADES CRITERIA

| | |
|----------|--|
| Grades | Rustic / Rustic A / Premier |
| Rustic | <p>Large and frequent knots including large, filled knots become a feature of the overall look. Rustic grade allows for a wide range of variation in colour and grain. The colour of the filler is intended to compliment the colour of the wood and may vary from batch to batch.</p> <ul style="list-style-type: none"> • Knots up to 80mm • Filled knots, cracks, and other imperfections • Centre core • Natural colour variation • Sapwood up to max. 25mm (on long side of boards) |
| Rustic A | <p>Rustic A grade is a selection of premier grade and 'good' rustic grade material. It contains knots including filled knots up to 40mm in size. The colour of the filler is intended to compliment the colour of the wood.</p> <ul style="list-style-type: none"> • Knots up to 40mm, including filled knots • Occasional, small cracks up to 20mm • Natural colour variation • Occasional sapwood up to max. 10mm |
| Premier | <p>Premier grade has an even appearance with very few, small knots. The natural variation is limited, though can be more visible on fumed oak.</p> <ul style="list-style-type: none"> • Occasional knots up to 15mm • Occasional, small cracks up to 20mm • Natural colour variation • No sapwood <p>Please note the selection process of prime/ premier grade boards wider than 245mm is usually more relaxed. The aim is to select calm boards with the minimum number of knots and grain variation.</p> |



STAIR SOLUTIONS

| | |
|--|--|
|  | Nose Dr Dutch Bullnose, round |
|  | Nose Dp Dutch Bullnose, pencil round |
|  | Nose Vr Victorian Bullnose, round |
|  | Nose Vp Victorian Bullnose, pencil round |
|  | Nose Sp Square Nose (no overhang), pencil round |
|  | Nose Se Square Nose (no overhang), bevelled |
|  | Custom treads available on request |

COLOUR VARIATION

| | |
|-------|---|
| Fumed | <p>The production process involves fuming with ammonia. This process results in colour variation between the boards / parquet pieces.</p> <p>Please read our installation guide for information on how to achieve a harmonious looking floor.</p> |
|-------|---|

PACK SIZE

Varied, between 1.6-2.5m²,
 Varied, depending on parquet size and pieces per pack

INSTALLATION METHODS

| | |
|--------------------------------------|--|
| Fixed installation | Secretly nailed or fully bonded. |
| Fully bonded over underfloor heating | <p>Suitable for installation over underfloor heating. Floors must be fully bonded to the substrate. The temperature of the floor surface must not exceed 27 degrees.</p> <p>Please refer to our comprehensive installation guide for more information.</p> |

RECOMMENDED OIL FOR TOPCOAT

Osmo Polyx Hardwax Oil Clear Semi-Matt 3065 applied by roller/ brush

Please read our guide on post installation requirements and application of the topcoat of oil.

MAINTENANCE

For regular damp mopping use the Osmo Wash & Care Soap

Please read the maintenance guide/o+m available from Waxed Floors.