

# Oak Ivory

## PRODUCT DETAILS

Species European Oak

Construction 3-layer engineered (softwood core)

Texture Brushed

Patterns Boards / Boards in mixed widths



Boards



Boards  
in  
mixed  
widths

Boards Width 160mm / 195mm / 245mm  
Boards Lengths Fixed 2200mm  
Herringbone sizes Not available  
Chevron sizes Not available

Depth / top layer (+/- 0.5mm) 15 / 4mm (15mm depth with a wear layer of +/- 4mm)\*\*  
\* Maximum board width: 220mm  
\*\* Maximum board width: 285mm

Edge profile Micro bevel

## TECHNICAL CRITERIA

Origin Germany




Formaldehyde Emission E1  
Engineered floors classified as E1 do not emit more than 0.1 ppm of formaldehyde into the ambient air and are 100% safe for interior use.

Certification FSC (Forest Stewardship Council) – certification on request, PEFC, EU and UK Timber Regulation compliant




Oak Ivory, brushed

**GRADES CRITERIA**

Grades	Rustic / Classic / Prime	
Rustic	<p>Large and frequent knots including large, filled knots become a feature of the overall look. Rustic grade allows for a wide range of variation in colour and grain. The colour of the filler is intended to compliment the colour of the wood. The filler from this manufacturer based in Germany is typically brown or black in colour.</p> <ul style="list-style-type: none"> <li>• Knots up to 80mm</li> <li>• Filled knots, cracks, and other imperfections</li> <li>• Natural colour variation</li> <li>• No sapwood</li> </ul>	
Classic	<p>Classic grade is a selection of prime grade and 'good' rustic grade material. It contains small knots including filled knots. The colour of the filler is intended to compliment the colour of the wood. The filler from this manufacturer based in Germany is typically brown or black in colour.</p> <ul style="list-style-type: none"> <li>• Knots up to 40mm, including filled knots</li> <li>• Natural colour variation</li> <li>• No sapwood</li> </ul>	
Prime	<p>Prime grade has an even appearance with very few, small knots. The natural variation is limited, though can be more visible on fumed oak.</p> <ul style="list-style-type: none"> <li>• Occasional knots up to 10mm</li> <li>• Natural colour variation</li> </ul> <p>The grading rules for boards wider than 245mm are less stringent. The aim is to select wide and long boards with a calm appearance. Extra wide and long boards in prime grade may contain occasional knots up to 30mm in size.</p>	

**STAIR SOLUTIONS**

	<p>Nose Se Square Nose (no overhang), bevelled</p>
---	--

**COLOUR VARIATION**

Non-fumed	<p>Non-fumed tones have less variation in colour compared to fumed tones. Please note, the natural variation can vary between batches.</p> <p>Please read our installation guide for information on how to achieve a harmonious looking floor.</p>
-----------	--

**PACK SIZE**

- 2.11m<sup>2</sup> for 160mm width,
- 2.57m<sup>2</sup> for 195mm width,
- 3.23m<sup>2</sup> for 245mm width

The company reserves the right to change this specification at any time without prior notice to third parties. The image are intended as a guide only and should not be regarded as absolutely accurate.

## INSTALLATION METHODS

---

Fixed installation	Secretly nailed or fully bonded.
Fully bonded over underfloor heating	Suitable for installation over underfloor heating. Floors must be fully bonded to the substrate. The temperature of the floor surface must not exceed 27 degrees.
Floating on underlay	Possible, up to a board width of 245mm. Please refer to our comprehensive <a href="#">installation guide</a> for more information.

## RECOMMENDED OIL FOR TOPCOAT

---

Floorservice Maintenance oil Antique White,  
Osmo Polyx Hardwax Oil Raw Transparent 3044 applied by  
floor buffer/ white pad

Please read our guide on post installation requirements and  
application of the topcoat of oil.

## MAINTENANCE

---

For regular damp mopping use the Osmo Wash & Care  
Soap

Please read the maintenance guide/o+m available from  
Waxed Floors.