



# Oak Ivory

## PRODUCT DETAILS


Species	European Oak
Construction	Plywood engineered (birch)
Texture	Brushed
Patterns	Boards / Boards in mixed widths / Chevron / Herringbone / Versailles panel




Boards




Boards in mixed widths



Chevron



Herringbone



Versailles panel

Boards Width	120mm / 140mm / 160mm / 180mm / 200mm / 220mm / 240mm / 260mm / 280mm / 300mm
Boards Lengths	Varied 1500 – 2500mm / Long boards available on request
Herringbone sizes	90 x 450mm / 120 x 600mm / 150 x 750mm
Chevron sizes	150 x 750mm / 120 x 600mm

Depth / top layer (+/- 0.5mm)	15 / 4mm (15mm depth with a wear layer of +/- 4mm)**, 20 / 5mm (20mm depth with a wear layer of +/- 5mm)
-------------------------------	---

\* Maximum board width: 220mm

\*\* Maximum board width: 285mm

Edge profile	Micro bevel
--------------	-------------

## TECHNICAL CRITERIA

Origin	Germany
Formaldehyde Emission	E1 Engineered floors classified as E1 do not emit more than 0.1 ppm of formaldehyde into the ambient air and are 100% safe for interior use.
Certification	FSC (Forest Stewardship Council) – certification on request, PEFC, EU and UK Timber Regulation compliant

The company reserves the right to change this specification at any time without prior notice to third parties. The image are intended as a guide only and should not be regarded as absolutely accurate.







Oak Ivory, brushed

**GRADES CRITERIA**

Grades	Rustic / Rustic A / Premier
Rustic	<p>Large and frequent knots including large, filled knots become a feature of the overall look. Rustic grade allows for a wide range of variation in colour and grain. The colour of the filler is intended to compliment the colour of the wood and may vary from batch to batch.</p> <ul style="list-style-type: none"> <li>• Knots up to 80mm</li> <li>• Filled knots, cracks, and other imperfections</li> <li>• Centre core</li> <li>• Natural colour variation</li> <li>• Sapwood up to max. 25mm (on long side of boards)</li> </ul>
Rustic A	<p>Rustic A grade is a selection of premier grade and 'good' rustic grade material. It contains knots including filled knots up to 40mm in size. The colour of the filler is intended to compliment the colour of the wood.</p> <ul style="list-style-type: none"> <li>• Knots up to 40mm, including filled knots</li> <li>• Occasional, small cracks up to 20mm</li> <li>• Natural colour variation</li> <li>• Occasional sapwood up to max. 10mm</li> </ul>
Premier	<p>Premier grade has an even appearance with very few, small knots. The natural variation is limited, though can be more visible on fumed oak.</p> <ul style="list-style-type: none"> <li>• Occasional knots up to 15mm</li> <li>• Occasional, small cracks up to 20mm</li> <li>• Natural colour variation</li> <li>• No sapwood</li> </ul> <p>Please note the selection process of prime/ premier grade boards wider than 245mm is usually more relaxed. The aim is to select calm boards with the minimum number of knots and grain variation.</p>



**STAIR SOLUTIONS**

	<p>Nose Se Square Nose (no overhang), bevelled</p>
	<p>Nose Dp Dutch Bullnose, pencil round</p>
	<p>Nose Vr Victorian Bullnose, round</p>
	<p>Custom treads available on request</p>

**COLOUR VARIATION**

## Non-fumed

Non-fumed tones have less variation in colour compared to fumed tones. Please note, the natural variation can vary between batches.

Please read our installation guide for information on how to achieve a harmonious looking floor.

## PACK SIZE

---

Varied, between 1.6-2.5m<sup>2</sup>

## INSTALLATION METHODS

---

Fixed installation	Secretly nailed or fully bonded.
Fully bonded over underfloor heating	Suitable for installation over underfloor heating. Floors must be fully bonded to the substrate. The temperature of the floor surface must not exceed 27 degrees.
Floating on underlay	Possible, up to a board width of 245mm.  Please refer to our comprehensive <a href="#">installation guide</a> for more information.

## RECOMMENDED OIL FOR TOPCOAT

---

Floorservice Maintenance oil Antique White,  
Osmo Polyx Hardwax Oil Raw Transparent 3044 applied by  
floor buffer/ white pad

Please read our guide on post installation requirements and  
application of the topcoat of oil.

## MAINTENANCE

---

For regular damp mopping use the Osmo Wash & Care  
Soap

Please read the maintenance guide/o+m available from  
Waxed Floors.