



# Oak Rust

## PRODUCT DETAILS


|              |   |
|--------------|---|
| Species      | European Oak  |
| Construction | Plywood engineered (birch) / 3-layer engineered (softwood core)                       |
| Texture      | Brushed   |
| Patterns     | 4s panel / Boards / Boards in mixed widths / Chevron / Herringbone / Versailles panel |




4s panel




Boards




Boards in mixed widths



Chevron



Herringbone



Versailles panel

|                   |   |
|-------------------|---|
| Boards Width      | 160mm / 180mm / 195mm / 220mm / 240mm / 245mm / 260mm / 280mm / 300mm / 350mm / 400mm / 450mm               |
| Boards Lengths    | Varied 1500 - 2500mm / Fixed 2200mm / Varied 1500 - 3500mm / Varied 2000 - 5000mm                           |
| Herringbone sizes | 70 x 350mm / 90 x 450mm / 120 x 600mm / 140 x 700mm / 140 x 980mm / 150 x 750mm / 175 x 875mm / 180 x 900mm |
| Chevron sizes     | 90 x 450mm / 120 x 600mm / 140 x 700mm / 140 x 980mm / 150 x 750mm / 175 x 875mm / 180 x 900mm              |

|                               |   |
|-------------------------------|---|
| Depth / top layer (+/- 0.5mm) | 13 / 4mm (13mm depth with a wear layer of +/- 4mm)*, 15 / 4mm (15mm depth with a wear layer of +/- 4mm)**, 20 / 6mm (20mm depth with a wear layer of +/- 6mm), 20 / 5mm (20mm depth with a wear layer of +/- 5mm) |
|-------------------------------|---|

\* Maximum board width: 220mm

\*\* Maximum board width: 285mm

|              |  |
|--------------|--|
| Edge profile | Micro bevel,<br>No bevel (square edge) |
|--------------|--|



Oak Rust, brushed

**TECHNICAL CRITERIA**








|                       |   |
|-----------------------|---|
| Origin                | Europe (Germany, Holland or Poland)   |
| Formaldehyde Emission | E1<br>Engineered floors classified as E1 do not emit more than 0.1 ppm of formaldehyde into the ambient air and are 100% safe for interior use. |
| Certification         | FSC (Forest Stewardship Council) – certification on request, PEFC, EU and UK Timber Regulation compliant  |

**GRADES CRITERIA**

|         |   |
|---------|---|
| Grades  | Rustic / Classic / Prime  |
| Rustic  | <p>Large and frequent knots including large, filled knots become a feature of the overall look. Rustic grade allows for a wide range of variation in colour and grain. The colour of the filler is intended to compliment the colour of the wood. The filler from this manufacturer based in Germany is typically brown or black in colour.</p> <ul style="list-style-type: none"> <li>• Knots up to 80mm</li> <li>• Filled knots, cracks, and other imperfections</li> <li>• Natural colour variation</li> <li>• No sapwood</li> </ul> |
| Classic | <p>Classic grade is a selection of prime grade and 'good' rustic grade material. It contains small knots including filled knots. The colour of the filler is intended to compliment the colour of the wood. The filler from this manufacturer based in Germany is typically brown or black in colour.</p> <ul style="list-style-type: none"> <li>• Knots up to 40mm, including filled knots</li> <li>• Natural colour variation</li> <li>• No sapwood</li> </ul>  |
| Prime   | <p>Prime grade has an even appearance with very few, small knots. The natural variation is limited, though can be more visible on fumed oak.</p> <ul style="list-style-type: none"> <li>• Occasional knots up to 10mm</li> <li>• Natural colour variation</li> </ul> <p>The grading rules for boards wider than 245mm are less stringent. The aim is to select wide and long boards with a calm appearance. Extra wide and long boards in prime grade may contain occasional knots up to 30mm in size.</p>                              |



**STAIR SOLUTIONS**

|  |  |
|--|--|
|  | Nose Dr<br>Dutch Bullnose, round                   |
|  | Nose Dp<br>Dutch Bullnose, pencil round            |
|  | Nose Vr<br>Victorian Bullnose, round               |
|  | Nose Vp<br>Victorian Bullnose, pencil round        |
|  | Nose Sp<br>Square Nose (no overhang), pencil round |
|  | Nose Se<br>Square Nose (no overhang), bevelled     |
|  | Custom treads available on request                 |

**COLOUR VARIATION**

|           |  |
|-----------|--|
| Non-fumed | <p>Non-fumed tones have less variation in colour compared to fumed tones. Please note, the natural variation can vary between batches.</p> <p>Please read our installation guide for information on how to achieve a harmonious looking floor.</p> |
|-----------|--|

**PACK SIZE**

Varied, between 1.6-2.5m<sup>2</sup>,  
 Varied, depending on parquet size and pieces per pack,  
 2.11m<sup>2</sup> for 160mm width,  
 2.57m<sup>2</sup> for 195mm width,  
 3.23m<sup>2</sup> for 245mm width

**INSTALLATION METHODS**

|                                      |  |
|--------------------------------------|--|
| Fixed installation                   | Secretly nailed or fully bonded.   |
| Fully bonded over underfloor heating | <p>Suitable for installation over underfloor heating. Floors must be fully bonded to the substrate. The temperature of the floor surface must not exceed 27 degrees.</p> <p>Please refer to our comprehensive <a href="#">installation guide</a> for more information.</p> |

### RECOMMENDED OIL FOR TOPCOAT

---

Floorservice Maintenance oil Clear,  
Osmo Maintenance Oil Clear Satin 3081,  
Osmo Polyx Hardwax Oil Clear Semi-Matt 3065 applied by  
roller/ brush,  
Osmo Polyx Hardwax Oil Clear Satin 3032 applied by roller/  
brush

Please read our guide on post installation requirements and  
application of the topcoat of oil.

### MAINTENANCE

---

For regular damp mopping use the Osmo Wash & Care  
Soap

Please read the maintenance guide/o+m available from  
Waxed Floors.