



Oak Rust

PRODUCT DETAILS


Species	European Oak
Construction	Plywood engineered (birch) / 3-layer engineered (softwood core)
Texture	Brushed
Patterns	4s panel / Boards / Boards in mixed widths / Chevron / Herringbone / Versailles panel




4s panel




Boards




Boards in mixed widths



Chevron



Herringbone



Versailles panel

Boards Width	160mm / 180mm / 195mm / 220mm / 240mm / 245mm / 260mm / 280mm / 300mm / 350mm / 400mm / 450mm / 140mm
Boards Lengths	Varied 1500 – 2500mm / Fixed 2200mm / Varied 1500 – 3500mm / Varied 2000 – 5000mm
Herringbone sizes	70 x 350mm / 90 x 450mm / 120 x 600mm / 140 x 700mm / 140 x 980mm / 150 x 750mm / 175 x 875mm / 180 x 900mm
Chevron sizes	90 x 450mm / 120 x 600mm / 140 x 700mm / 140 x 980mm / 150 x 750mm / 175 x 875mm / 180 x 900mm

Depth / top layer (+/- 0.5mm)	13 / 4mm (13mm depth with a wear layer of +/- 4mm)*, 15 / 4mm (15mm depth with a wear layer of +/- 4mm)**, 20 / 6mm (20mm depth with a wear layer of +/- 6mm), 20 / 5mm (20mm depth with a wear layer of +/- 5mm)
-------------------------------	---

* Maximum board width: 220mm

** Maximum board width: 285mm

Edge profile	Micro bevel, No bevel (square edge)
--------------	--



Oak Rust, brushed

TECHNICAL CRITERIA








Origin	Europe (Germany, Holland or Poland)
Formaldehyde Emission	E1 Engineered floors classified as E1 do not emit more than 0.1 ppm of formaldehyde into the ambient air and are 100% safe for interior use.
Certification	FSC (Forest Stewardship Council) – certification on request, PEFC, EU and UK Timber Regulation compliant

GRADES CRITERIA

Grades	Rustic / Classic / Prime
Rustic	<p>Large and frequent knots including large, filled knots become a feature of the overall look. Rustic grade allows for a wide range of variation in colour and grain. The colour of the filler is intended to compliment the colour of the wood. The filler from this manufacturer based in Germany is typically brown or black in colour.</p> <ul style="list-style-type: none"> • Knots up to 80mm • Filled knots, cracks, and other imperfections • Natural colour variation • No sapwood
Classic	<p>Classic grade is a selection of prime grade and 'good' rustic grade material. It contains small knots including filled knots. The colour of the filler is intended to compliment the colour of the wood. The filler from this manufacturer based in Germany is typically brown or black in colour.</p> <ul style="list-style-type: none"> • Knots up to 40mm, including filled knots • Natural colour variation • No sapwood
Prime	<p>Prime grade has an even appearance with very few, small knots. The natural variation is limited, though can be more visible on fumed oak.</p> <ul style="list-style-type: none"> • Occasional knots up to 10mm • Natural colour variation <p>The grading rules for boards wider than 245mm are less stringent. The aim is to select wide and long boards with a calm appearance. Extra wide and long boards in prime grade may contain occasional knots up to 30mm in size.</p>



STAIR SOLUTIONS

	Nose Dr Dutch Bullnose, round
	Nose Dp Dutch Bullnose, pencil round
	Nose Vr Victorian Bullnose, round
	Nose Vp Victorian Bullnose, pencil round
	Nose Sp Square Nose (no overhang), pencil round
	Nose Se Square Nose (no overhang), bevelled
	Custom treads available on request

COLOUR VARIATION

Non-fumed	<p>Non-fumed tones have less variation in colour compared to fumed tones. Please note, the natural variation can vary between batches.</p> <p>Please read our installation guide for information on how to achieve a harmonious looking floor.</p>
-----------	--

PACK SIZE

Varied, between 1.6-2.5m²,
 Varied, depending on parquet size and pieces per pack,
 2.11m² for 160mm width,
 2.57m² for 195mm width,
 3.23m² for 245mm width

INSTALLATION METHODS

Fixed installation	Secretly nailed or fully bonded.
Fully bonded over underfloor heating	<p>Suitable for installation over underfloor heating. Floors must be fully bonded to the substrate. The temperature of the floor surface must not exceed 27 degrees.</p> <p>Please refer to our comprehensive installation guide for more information.</p>

RECOMMENDED OIL FOR TOPCOAT

Floorservice Maintenance oil Clear,
Osmo Maintenance Oil Clear Satin 3081,
Osmo Polyx Hardwax Oil Clear Semi-Matt 3065 applied by
roller/ brush,
Osmo Polyx Hardwax Oil Clear Satin 3032 applied by roller/
brush

Please read our guide on post installation requirements and
application of the topcoat of oil.

MAINTENANCE

For regular damp mopping use the Osmo Wash & Care
Soap

Please read the maintenance guide/o+m available from
Waxed Floors.