



Oak Shingle

PRODUCT DETAILS


Species	European Oak
Construction	Plywood engineered (birch)
Texture	Brushed
Patterns	4s panel / Boards / Boards in mixed widths / Chevron / Herringbone / Versailles panel




4s panel




Boards




Boards in mixed widths



Chevron



Herringbone



Versailles panel

Boards Width	200mm / 250mm / 300mm / 350mm / 400mm
Boards Lengths	Varied 1500 – 3500mm
Herringbone sizes	120 x 600mm / 120 x 840mm / 140 x 700mm / 140 x 980mm
Chevron sizes	120 x 600mm / 120 x 840mm / 140 x 700mm / 140 x 980mm

Depth / top layer (+/- 0.5mm)	16 / 4mm (16mm depth with a wear layer of +/- 4mm)**, 20 / 5mm (20mm depth with a wear layer of +/- 5mm)
-------------------------------	---

* Maximum board width: 220mm

** Maximum board width: 285mm

Edge profile	Micro bevel, Square bevel
--------------	------------------------------

TECHNICAL CRITERIA

Origin	Poland
Formaldehyde Emission	E1 Engineered floors classified as E1 do not emit more than 0.1 ppm of formaldehyde into the ambient air and are 100% safe for interior use.
Certification	FSC (Forest Stewardship Council) – certification on request, PEFC, EU and UK Timber Regulation compliant

The company reserves the right to change this specification at any time without prior notice to third parties. The image are intended as a guide only and should not be regarded as absolutely accurate.



Oak Shingle, brushed

GRADES CRITERIA

Grades	Rustic / Classic / Prime
Rustic	<p>Large and frequent knots including large, filled knots become a feature of the overall look. Rustic grade allows for a wide range of variation in colour and grain. The colour of the filler is intended to compliment the colour of the wood. The filler from this manufacturer based in Germany is typically brown or black in colour.</p> <ul style="list-style-type: none"> • Knots up to 80mm • Filled knots, cracks, and other imperfections • Natural colour variation • No sapwood
Classic	<p>Classic grade is a selection of prime grade and 'good' rustic grade material. It contains small knots including filled knots. The colour of the filler is intended to compliment the colour of the wood. The filler from this manufacturer based in Germany is typically brown or black in colour.</p> <ul style="list-style-type: none"> • Knots up to 40mm, including filled knots • Natural colour variation • No sapwood
Prime	<p>Prime grade has an even appearance with very few, small knots. The natural variation is limited, though can be more visible on fumed oak.</p> <ul style="list-style-type: none"> • Occasional knots up to 10mm • Natural colour variation <p>The grading rules for boards wider than 245mm are less stringent. The aim is to select wide and long boards with a calm appearance. Extra wide and long boards in prime grade may contain occasional knots up to 30mm in size.</p>



STAIR SOLUTIONS



Nose Se
Square Nose (no overhang), bevelled



Custom treads available on request



Nose Vr
Victorian Bullnose, round



Nose Vp
Victorian Bullnose, pencil round

COLOUR VARIATION

Fumed

The production process involves fuming with ammonia. This process results in colour variation between the boards / parquet pieces.

Please read our installation guide for information on how to achieve a harmonious looking floor.

PACK SIZE

Varied, between 1.6-2.5m²,
Varied, depending on parquet size and pieces per pack

INSTALLATION METHODS

Fixed installation	Secretly nailed or fully bonded.
Fully bonded over underfloor heating	Suitable for installation over underfloor heating. Floors must be fully bonded to the substrate. The temperature of the floor surface must not exceed 27 degrees. Please refer to our comprehensive installation guide for more information.

RECOMMENDED OIL FOR TOPCOAT

Floorservice Maintenance oil Antique White

Please read our guide on post installation requirements and application of the topcoat of oil.

MAINTENANCE

For regular damp mopping use the Osmo Wash & Care Soap

Please read the maintenance guide/o+m available from Waxed Floors.